

Nexus 440 Brushable Skirting Contact

TECHNICAL DATA SHEET

DESCRIPTION

Nexus 440 is a solvent based neoprene contact adhesive used for fixing vinyl skirting and other common flooring materials where a quick contact bond is required to plaster, timber and metal substrates.

METHOD OF APPLICATION

IMPORTANT: Ensure the ambient temperature is between 10°C and 30°C with low to moderate humidity, conditions outside this range may lead to failures caused by humidity blushing.

To obtain the best results, the materials to be bonded should be dry, clean and free from dust, grit, oil, grease and other contaminants that may affect final bond.

Apply an even coat of adhesive to both surfaces by brush or roller. On porous surfaces a second application may be required.

Allow solvent to evaporate and adhesive to become tacky. Place the surfaces together making sure that they are correctly positioned beforehand as no adjustment is possible after the surface has met.

Press both surfaces together, making sure sufficient pressure is applied to bring both surfaces into close contact.

CLEAN UP

Clean tools immediately after use with **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

Dried adhesive may be softened using a **Nexus Adhesive Remover** or **Nexus 490 Solvent Cleaner**.

IMPORTANT: Do not use Nexus 490 Solvent Cleaner directly on finish floorcovering, as the solvent cleaner can potentially cause damage to the surface.

TYPICAL PROPERTIES

Appearance	Light yellow brush-able liquid
Coverage	3 - 4m ² per litre
Open Time	20 – 30 minutes at 50% Relative Humidity and 21 °C
Curing Time	24 Hours
Packaging	1, 4 & 20 Litre
Shelf Life	12 months in sealed container at 20 °C

Note: Always carry out your own test to confirm suitability of this product with your application. Additional information on physical properties, health hazards, storage, handling and transport is available in the Safety Data Sheet (SDS), available on request.

June 2024

Nexus Adhesives Pty Ltd
ABN 61 121 120 036

42 Healey Road
Dandenong South VIC 3175 Australia
Tel +61 3 9706 4022
Fax +61 3 9706 4122
www.nexusadhesives.com.au
info@nexusadhesives.com.au